

28" Widescreen LCD Display

HG-281DPB







































Technical Specifications

1. Display Size/Type	27.5" Widescreen Active Matrix TFT LCD	20. Input Voltage	AC 100-240V, 50/60Hz Autodetect
2. Resolution	1920 x 1200 (WXGA+)	21. Power Consumption	100W Maximum
3. Aspect Ratio	16:10	22. Operating Temperature	5°C~35°C / 41°F~95°F
4. Pixel Pitch	0.309(H)mm x 0.309(V)mm	23. Humidity	10%~85%
5. Brightness	500cd/m²	24. Net Dimensions	26.4"(W) x 19.2"(H) x 8.4"(D)
6. Response Time	3ms Xcelerate Overdrive, 5ms (Typical)	25. Net Weight	24 lbs.
7. Contrast Ratio	X-Contrast 2400:1/DCR, (800:1 Typical)	26. Gross Dimensions	30"(W) x 24"(H) x 11"(D)
8. Displayable Colors	16.7 Million	27. Gross Weight	31.7 lbs.
9. Viewing Angle (H/V)	160°/160°	28. Certifications	FCC, UL, C-UL, CE, BSMI, C-Tick, TCO'06
10. Color Temperature	9300K, 6500K, 5500K, User Mode		VCCI, CB, CCC, NEMKO/Bau-Mark, MIC,
11. Panel Treatment	Anti-Glare Hardcoating		RoHS, EPA Energy Star, Vista Premium
12. Horizontal Frequency	24kHz to 80kHz	29. Package Contents	HG-281DPB, Cables (VGA, HDMI to DVI, VGA to YPbPr, 3.5mm Audio, 3.5mm to RCA Audio, and Power), User Manual CD-ROM,
13. Vertical Frequency	56Hz to 75Hz		
14. Video Input(s)	15-Pin D-SUB (VGA), HDMI w/ HDCP		
15. Speakers	2.5W x 2 Channel Built-in Stereo		Quick Start Guide, Warranty Card
16. Headphone Out	Yes	30. UPC Code	842651002114
17. Tilt	0°~20°	31. Warranty	3-Year Limited (3-Year Parts/Labor,
18. Kensington Slot	Yes		1-Year LCD/Backlight)
19. VFSA Mounting	200mm x 100mm		









